



12. SAR for land subsidence

SAR Interferometry (InSAR) – use of phase for change detection

Interferometric Synthetic Aperture Radar (InSAR) also known as SAR Interferometry, is the measurement of signal phase change between two images acquired over the same area at different time. When a point on the ground moves, it alters the distance between the sensor and the point, resulting in a change in the signal phase.



Differential Interferometry

- Differential Interferometry or DInSAR is a intererometric technique in which topographic effects are compensated by using a Digital Elevation Model (DEM)
- Small surface deformations in the Earth's surface, such as subsidence, uplift, or deformation, can be detected with high precision, sometimes down to the millimeter level
- Particularly useful for monitoring ground movements caused by natural phenomena like earthquakes, landslides, or human activities such as mining or groundwater extraction.



https://britgeopeople.blogspot.com/2017/01/assessing-ground-motion-fromspaceby.html, https://dges.carleton.ca/courses/IntroSAR/SECTION%207%20-%20Carleton%20SAR%20Training%20-%20InSAR%20Theory%20-%20Final.pd

- In order to correlate the interferometric phase with topographic height, the phase must undergo an unwrapping process
- Then, the proper 2p phase "ambiguity" must be determined
- The altitude of ambiguity refers to the altitude difference that causes a change in the interferometric phase
- Phase unwrapping resolves this ambiguity by integrating the phase difference between adjacent pixels

$$\begin{split} \Delta \phi_{topo} &= \frac{2\pi p}{\lambda} (\rho_1 - \rho_2) = \frac{2\pi p}{\lambda} \vec{b} \cdot \vec{l} \\ \Delta \phi_{meas} &= \mathrm{mod} \Big(\Delta \phi_{topo}, 2\pi \Big) \\ \Delta \phi_{unwrap}(s, \rho) &= \Delta \phi_{topo}(s, \rho) + \Delta \phi_{const} \end{split}$$



Phase unwrapping



Consequently, unwrapped results should be interpreted as relative height or displacement between pixels in two images.

https://site.tre-altamira.com/insar/

Interferogram



One cycle of color represents one cycle of relative phase.

https://nisar.jpl.nasa.gov/mission/get-to-knowsar/interferometry/

- The SAR interferogram is created by multiplying each pixel of the first SAR image with the complex conjugate of the corresponding pixel in the second image
- Consequently, the amplitude of the interferogram is determined by the product of the amplitudes of the two images, while its phase, represents the difference in phase between the two images. This phase difference is caused by variations in path length due to differences in elevation, motion, or deformation.
- The resulting interference pattern, referred to as FRINGE, is represented within the range of $[-\pi, \pi]$.

Coherent Change Detection

SIR-C L and C-band Interferometry

- Simultaneous C and L band
- InSAR experiments have shown good correlation at L-band



ERS(C-band, 5.6 cm, VV)



https://media.springernature.com/lw 685/springer-static/image/ prt%3A978-3-030-58631-7%2F17 /MediaObjects/978-3-030-58631 -7_17_Part_Fig7-97_HTML.png

Applications of InSAR





Land surface



Crustal deformation



Forest monitoring





SAR Tomography

https://gisgeography.com/free-global-dem-data-sources/, https://www.esa.int/ESA_Multimedia/Images/2014/12/Mexico_City_subsidence, https://www.esa.int/ESA_Multimedia/Images/2019/07 /lce_velocity_maps _of_Greenland, https://www.esa.int/ESA_Multimedia/Images/2017/04/Sentinel-1_sees_Mocoa_landslide, https://www.esa.int/Applications/Observing_the_Earth/Mapping_forest_structure_from_space

Applications of InSAR

Subsidence of Italy



With advances in the methods of interferometry, subsidence of entire countries can now be mapped. This image shows the average displacement rates over millions of permanent scatterers identified over Italy using data from ESA's ERS missions (1992–2001). The project was financed by the Italian Ministry of the Environment and carried out by e-GEOS, TRE and Compulab.

CREDIT: Tele-Rilevamento Europa (TRE)

Crustal deformation

- Gradual changes in the Earth's crust over time, typically caused by:
 - natural processes tectonic plate movements, earthquakes, volcanic activity
 - human-induced activities: mining or groundwater extraction
- Displacements of the Earth's surface: including uplift, subsidence, faulting, folding, or other
- Key indicator to understand the dynamic processes occurring beneath the Earth's surface and to assess the potential for seismic hazards



Crustal deformation

Landslip and land subsidence



Downward movement of soil or sinking of the land from its previous level

https://spacegen.guru/land slip-and-land-subsidence/

Monitoring of groundwater extraction



Larissa's ups and downs

For example, this image shows the rate of ground displacement between 2015 and 2020 in and around Larissa, the capital of the Thessaly region in Greece. While the southern outskirts of Larissa experience some uplift, the village of Chalki to the southeast subsided by an average of 40 mm a year, largely a result of groundwater as extraction. Ampelonas to the northwest also experienced subsidence.

CREDIT: contains modified Copernicus Sentinel data (2015–2020), processed by EGMS/ESA

Infrastructure monitoring



https://insar.space/projects/

Monitoring of coal mining activity



Downward movement of soil or sinking of the land from its previous level

https://spacegen.guru/land slip-and-land-subsidence/

https://insar.space/projects/

Monitoring of coal mining activity



on 'Persistent Scatterer Based Interferometry' radar data from the Copernicus Sentinel-1 mission, the map shows how the land surface shifted in millimetres a year between 2014 and 2019 in the Ruhr in Germany. The subsidence shown in red is because of open pit lignite mining accompanied by groundwater lowering. Blue patches in the adjacent area are likely to be related to the rise of groundwater after mining activities ceased.

CREDIT: contains modified Copernicus Sentinel data (2014–19), processed by BGR (2020)

Monitoring the sinking



Using images that Sentinel-1A acquired between November 2014 and April 2016, this map shows subsidence (red) and uplift (blue) in the northeast of the Netherlands.

https://www.esa.int/Applications/Observing_the_Earth/Copernicus/Sentinel-1/Mapping_that_sinking_feeling

Monitoring of ground displacements over the drainage pots



SAGD field in Alberta. SqueeSAR[®] analysis provided measurements of ground displacement over the drainage pads.

https://site.tre-altamira.com/oil-gas-operations/

Monitoring displacements over active oil operations



Displacement over active oil operations. Red and blue indicate areas of rapid subsidence and heave detected by SAR satellites. © DLR e.V. 2009-2013 and © Airbus Defense and Space GmbH

https://site.tre-altamira.com/oil-gas-operations/

Volcano uplift and subsidence



Etna's uplift and subsidence

This image shows the rate of ground displacement between 2015 and 2020 around Mount Etna and surroundings on the Italian island of Sicily. While the volcano's western flank experienced some uplift, its eastern flank subsided, on average, 80 mm a year.

CREDIT: contains modified Copernicus Sentinel data (2015– 2020), processed by EGMS/ESA

For more information, see the tutorials: 12. Land subsidence mapping using SAR interferometry (InSAR) using the SNAP software









Thank you for the attention

ESA UNCLASSIFIED

A CARGE